

Stationary hydraulic lift **DHP - 1,0t**

v1

2013/01/23

The DHP hydraulic lift allows for the stepless lifting and lowering of materials in installation locations, loading and working stations with table dimensions approaching those of a EUR pallet. It makes it possible to maintain a constant working level during the loading or unloading of material. Lifting of the table is made possible by two hydraulic cylinders, powered by a compact electro-hydraulic unit, steered by a control unit on a stand. The control unit is equipped with lifting, lowering, and "EMERGENCY STOP" buttons.



TECHNICAL AND OPERATIONAL DATA:

Max load	kg	1000
Table dimensions (standard)	mm	860 x 130
Height when folded (standard)	mm	~ 225
Working interval (max)	mm	800
Lifting time	s	ok. 25 sek
Pressure in the hydraulic system	MPa	max 16
Noise level	dBA	ok. 72
Installed power	kW	1,1
Electric supply	V AC	3/N/PE, 400V 50Hz
Control voltage	V DC	24
Appliance mass	kg	~ 400

The lift can be equipped with roller conveyors, a rotating table, barriers, flaps, and other mechanisms, offered in a wide range of table dimensions and lifting heights depending on the client's needs.

Lifts are inspected according to appendix C of the PN-EN 1570:2002 standard – "SAFETY REQUIREMENTS REGARDING TABLE LIFTS", and have a CE COMPLIANCE DECLARATION and all necessary documents for UDT registration.